

Lyden Oil Company

Page 1 of 8 -

**Propylene Glycol** 

SDS Number: 909251

#### PRODUCT AND COMPANY INFORMATION

Product Name: Propylene Glycol
Revision Date: 09/25/2015
SDS Number: 909251

<u>Common Name:</u> Propylene Glycol - Industrial Grade

<u>CAS Number:</u> 57-55-6 <u>Product Code:</u> 909251

Synonyms: Propane-1,2-diol; methyl ethylene glycol; 1,2-dihydroxypropane; PG

#### **Company Identification:**

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION

Signal Word: None

Hazard Classes/Categories:

None

Hazard Statement(s):

2

None

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.



Lyden Oil Company

Page 2 of 8 -

**Propylene Glycol** 

SDS Number: 909251

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

3

#### **COMPOSITION / INFORMATION ON INGREDIENTS**

#### **Ingredients:**

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Propylene glycol	57-55-6	98-100

<sup>\*</sup>Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### 4 FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:

If symptoms develop, move victim to fresh air and keep in a position comfortable for breathing. If symptoms persist, obtain medical

attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

before reuse. Get medical attention if needed.

Eye Contact:

Rinse opened eye for at least 15 minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water and drink plenty of water to dilute. If

symptoms develop, obtain medical attention.



Lyden Oil Company

Page **3** of **8** –

**Propylene Glycol** 

SDS Number: 909251

Symptoms and Effects, both acute and delayed:

Acute - Mild eye, skin, and/or respiratory tract

irritation.

**Recommended Actions:** 

Treat symptomatically. Call a doctor or poison

control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may cause frothing and splattering and should only be used by experienced

fire fighters.

Possible Hazards During a Fire:

Vapors which ignite at or above the flash point are heavier than air and may travel along the ground. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** 

Avoid contact with skin, eyes, and clothing. Avoid

breathing vapors.

Keep away from sources of ignition.



Lyden Oil Company

Page **4** of **8** –

**Propylene Glycol** 

SDS Number: 909251

**Emergency Procedures:** 

Contain spilled material, collect in suitable and

properly labled containers.

**Environmental Precautions:** 

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material if released on the ground. Suppress vapors using water fog if released to the air. Notify all downstream users of possible contamination if released to waters. Treat contaminated absorbent

same as spilled product.

#### 7 HANDLING AND STORAGE

**Handling Precautions:** 

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder

container.

**Storage Requirements:** 

Keep container tightly sealed.
Keep away from sources of ignition.

#### EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Limits:** 

-57-55-6 Propylene Glycol (100%):

AIHA WEEL TWA - 10mg/m³ (aerosol)

**Engineering Controls:** 

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).



Lyden Oil Company

Page **5** of **8** -

**Propylene Glycol** 

SDS Number: 909251

#### Personal Protective Equipment:

Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated

clothing.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin. Use safety glasses and gloves.

In case of low exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device

that is independent of circulating air.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Colorless
Physical State: Liquid
Odor: Mild

Odor Threshold: Data not available pH: Data not available

Melting Point: -60° C Boiling Point: 187° C

Boiling Range: Data not available

Flash Point: 107° C

Evaporation Rate: 0.01 (where Butyl Acetate - 1)

Flammability: Data not available Flammability Limits: 2.6-12.5 % Vol. Vapor Pressure: <0.1 mmHg at 25 °C

Vapor Density: 2.62 Relative Density: 1.04

Solubilities: Completely miscible in water

Partition Coefficient: -0.92 (Log Kow)

Auto-Ignition Temperature: 371 °C

Decomposition Temperature: Data not available Viscosity: 0.581 cP at 20 °C

#### 10 STABILITY AND REACTIVITY

#### Stability:

Stable under normal conditions.



Lyden Oil Company

Page **6** of **8** ——

**Propylene Glycol** 

SDS Number: 909251

**Reactivity:** 

Reacts with strong oxidants, causing a fire hazard.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and

direct sunlight.

**Hazardous Reactions:** 

May react with hydrofluoric acid, nitric acid, and silver nitrate to form the explosive silver fulminate.

**Incompatible Materials:** 

Strong oxidizers.

**Decomposition Products:** 

Oxides of carbon.

#### 11

#### TOXICOLOGICAL INFORMATION

**Routes of Exposure:** 

This material is absorbed into the body by inhalation of its vapor, and by ingestion.

Exposure Effects:

May irritate the eyes causing redness and pain.

May cause mild irritation to the skin.

**Measures of Toxicity:** 

**Component Acute Toxicity Estimates:** 

-57-55-6 Propylene glycol:

Oral LD50: >5000 mg/kg (rat)
Dermal LD50: >2000 mg/kg (rabbit)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.



Lyden Oil Company

Page **7** of **8** –

**Propylene Glycol** 

SDS Number: 909251

#### 12 ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.

**Ecological Effects:** 

-57-55-6 Propylene glycol:

LC50 - Fathead minnow: >62000 mg/L (96 hours) LC50 - Daphnia magna: >43500 mg/L (48 hours)

#### 13 DISPOSAL CONSIDERATIONS

**Disposal Methods:** 

Dispose of waste material in accordance with all

local, state, and federal requirements.

**Disposal Containers:** 

Use properly approved container for disposal.

**Special Precautions:** 

Do not flush to surface waters or drains.

#### 14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

**Environmental Hazards:** 

Data not available

**Bulk Transport Guidance:** 

Data not available

**Special Precautions:** 

Not regulated by DOT.



Lyden Oil Company

Page 8 of 8 -

**Propylene Glycol** 

SDS Number: 909251

#### 15

#### REGULATORY INFORMATION

The following product components are cited on the Pennsylvania Hazardous Substances List and/or the Pennsylvania Environmental Hazardous Substances List and are present at levels which require reporting:

-57-55-6 Propylene glycol Listing: PA RTK 98-100%

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

#### 16

#### OTHER INFORMATION

Last Revision Date: 09/25/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.